



AR FILTRAZIONI

TODAY DATE:

COMPILER:



YOUR CUSTOMER		RIGHT/LEFT VERSION (easier side to open the door during spare parts change) LEGEND: L=left - R=right	WORKING AREA of the machine tool				TYPE OF POLLUTANT				TYPE OF METAL WORKING				EFFECTS CAUSED/ CAUSES BRINGING ABOUT			specify number of working shifts (1=8 hours - 2=16 hours - 3=24 hours) specify if "handle charging" or "bar feeding" (please write H for handle c. - B for Bar feeding)		
MACHINE TOOL			Prearranged suction hole of the machine tool (if there is) DIAM. MM.	OPEN	CLOSED	PARTIALLY CLOSED	DOUBLE	VOLUME of the working area in cubic metres	COOLANT LIQUID				STEEL	CAST IRON	ALUMINIUM	OTHER, TO BE SPECIFIED	A LOT OF LIQUID POLLUTANT		A LOT OF FUME	USE OF HIGH PRESSURE PUMPS
TYPE (lathe, machining centre, grinder, ...). For machining centre underline VERTICAL or ORIZONTAL	TRADEMARK and MODEL								STRAIGHT OIL	SPRAY MIX	EMULSIFIED OIL	DRY MACHINING PROCESS								
1			mm				m ³											bar		
2			mm				m ³											bar		
3			mm				m ³											bar		
4			mm				m ³											bar		
5			mm				m ³											bar		
6			mm				m ³											bar		
7			mm				m ³											bar		
8			mm				m ³											bar		